

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2003299577 A**

(43) Date of publication of application: **21.10.2003**

(51) Int. Cl. **A47J 31/52**
A47J 31/46

(21) Application number: **2002109019**

(22) Date of filing: **11.04.2002**

(71) Applicant: **UCC UESHIMA COFFEE CO LTD**

SANYO HOME TEC KK

SANYO ELECTRIC CO LTD

(72) Inventor: **SHIONO SHUNJI**

ITAKURA KOJI

IMAIZUMI YASUTOKU

FUKUDA TATSUHISA

SHIBAYAMA FUMIO

MATSUO KIYOSHI

(54) EXTRACTION DEVICE

water supplied to the extraction cup 100 is controlled by controlling a driving voltage of the gear pump 6.

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an extraction device capable of easily and accurately changing an amount of an obtained liquid extract and performing an extraction of liquid in a desired extraction time.

SOLUTION: Water supplied to a water storing tank 3 in the extraction device is fed into a hot water storing tank 5 through a pipe 51. The water fed into the hot water storing tank 5 is heated by a heater 50. A temperature of hot water positioned at the upper part in the hot water storing tank 5 is detected by a temperature sensor 54. Then, when a detected temperature of the temperature sensor 54 reaches a predetermined temperature, a gear pump 6 is driven to cause the hot water in the hot water storing tank 5 to be fed into the gear pump 6 through a flowing-out passage 53, a pipe 53 and a three-way solenoid valve 60. Further, the hot water is supplied to an extraction cup 100 through a pipe 63 and a feeding needle 65. An amount of hot

COPYRIGHT: (C)2004,JPO

